

CARTRIDGE

Model: 2050 A2P3 R

P/N 114000000

Combined filter with special snap-in connector for organic vapours having boiling point higher than 65°C, dusts, fumes, mists.

The cartridge shall be used in pairs with half masks **DUETTA** and **DUO** or full face masks type **TR 2002 CL2** and **TR 2002 CL3** with **DUPLA** adapter.



TECHNICAL DATA

Inhalation resistance at

15 l/min: 1.2 mbar at

47.5 l/min: 4.3 mbar

Duration at gases

Filter type	Class	Testing Gas	Testing Concentration (PPM)	Testing Flow (l/min)	Testing HR (%)	Breakthrough concentration (PPM)	Duration Required (min)	Duration Tested (min)
A	2	C ₆ H ₁₂	5000	15	70%	10	35	44

Performance particle filtration – long duration test

Filter type	Class	Testing Flow (l/min)	Testing Aerosol (%)	Penetration Max Allowed (%)	Penetration Max Measured
P R	3	47.5	NaCl	0.05	0.003
			Paraffin oil	0.05	0.002

Marking R means that the filter is reusable for more than one workshift.

Limitations for use

Do not use in areas where the oxygen concentration is lower than 17% in volume nor in presence of gases different from those clearly indicated.