

SET AC 190

Air line respirator with TR 2002
Mod. P/N 130010000



TECHNICAL DATA:

Mask: see specific data sheet

Flow regulator AC 95: flow can be set between 165 and 230 l/min, alarm for flow below 120 l/min. Available equipped with the standard Spasciani male quick coupling (P/N 932100000) or with Eurocoupling quick coupling (P/N 9321000CJ)

Corrugated hose TUR 60: length 60 cm.

Compressed air feeding hose 8x17: available in different lengths (max 50 m) and with standard Spasciani or Eurocoupling quick couplings.

Models and order P/Ns:

Length (m)	Hose provided with Spasciani quick couplings	Hose provided with Eurocoupling quick couplings
5	139290000	1392900CJ
10	139300000	1393000CJ
15	139340000	1393400CJ
20	139310000	1393100CJ
30	139330000	1393300CJ
50	139320000	1393200CJ



YOUR SAFETY MAKER

CLASSIFICATION

Certified as Class 4B device to EN 14594:2005, it complies with directive 89/686/EEC (PPE)

MARKING



MATERIALS

TR 2002 CL2 Mask

Outer face blank:	TPE
Panoramic Visor:	Polycarbonate
Inner Nose Cup:	TPE
Five arm head harness:	EPDM
Carrying strap:	PVC
AC 95 flow regulator:	Aluminium alloy nickel plated
EOD 55 filter silencer: and carbon)	Made of shockproof polypropylene and filtering material (filtering paper
Corrugated hose:	Moulded in polyurethane with screwed plastic connections
Overflow valve:	Made of moulded rubber with positive pressure valve
Compressed air feeding hoses:	EPDM hose 8 x 17, non toxic, fitted with safety quick connectors.

STORAGE

Store at temperatures between -20 and +50 °C and RH <80%.